

DOD Hazardous Materials Information System
DoD 6050.5-L
AS OF July 1998

FSC: 8010
NIIN: 00N084071
Manufacturer's CAGE: 0CUY5
Part No. Indicator: A
Part Number/Trade Name: WEATHER BOND EXTERIOR LATEX HOUSE PAINT, G2600-30279

=====
General Information
=====

Item Name:
Company's Name: ROSE TALBERT PAINT CO
Company's Street: 901 FRINK ST
Company's P. O. Box:
Company's City: CAYCE
Company's State: SC
Company's Country: US
Company's Zip Code: 29033
Company's Emerg Ph #: 800-255-3924
Company's Info Ph #: 803-796-0324
Distributor/Vendor # 1:
Distributor/Vendor # 1 Cage:
Distributor/Vendor # 2:
Distributor/Vendor # 2 Cage:
Distributor/Vendor # 3:
Distributor/Vendor # 3 Cage:
Distributor/Vendor # 4:
Distributor/Vendor # 4 Cage:
Safety Data Action Code: A
Safety Focal Point: N
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Status: SMJ
Date MSDS Prepared: 13MAR97
Safety Data Review Date: 23MAR98
Supply Item Manager:
MSDS Preparer's Name: MARY COUNTS
Preparer's Company: SAME
Preparer's St Or P. O. Box:
Preparer's City:
Preparer's State:
Preparer's Zip Code:
Other MSDS Number:
MSDS Serial Number: CGSDC
Specification Number:
Spec Type, Grade, Class:
Hazard Characteristic Code:
Unit Of Issue:
Unit Of Issue Container Qty:
Type Of Container:

Report for NIIN: 00N084071

Net Unit Weight:
NRC/State License Number:
Net Explosive Weight:
Net Propellant Weight-Ammo:
Coast Guard Ammunition Code:

=====

Ingredients/Identity Information

=====

Proprietary: NO
 Ingredient: TITANIUM OXIDE; (TITANIUM DIOXIDE)
 Ingredient Sequence Number: 01
 Percent: 17.40
 Ingredient Action Code: A
 Ingredient Focal Point: N
 NIOSH (RTECS) Number: XR2275000
 CAS Number: 13463-67-7
 OSHA PEL: 15 MG/M3 TDUST
 ACGIH TLV: 10 MG/M3 TDUST
 Other Recommended Limit: N/K

 Proprietary: NO
 Ingredient: ETHYLENE GLYCOL (SARA 313) (CERCLA) VP: 3.2
 Ingredient Sequence Number: 02
 Percent: 2.29
 Ingredient Action Code: A
 Ingredient Focal Point: N
 NIOSH (RTECS) Number: KW2975000
 CAS Number: 107-21-1
 OSHA PEL: N/K (FP N)
 ACGIH TLV: C 50 PPM, VAPOR
 Other Recommended Limit: N/K

 Proprietary: NO
 Ingredient: VOLATILE ORGANIC COMPOUND: 1.073
 Ingredient Sequence Number: 03
 Percent: N/K
 Ingredient Action Code: A
 Ingredient Focal Point: N
 NIOSH (RTECS) Number: 9999999VO
 CAS Number:
 OSHA PEL: N/K (FP N)
 ACGIH TLV: N/K (FP N)
 Other Recommended Limit: N/K

 Proprietary: NO
 Ingredient: SPILL PROC: KEEP OUT OF DRAINS, SEWERS/WATERWAYS. CONT FIRE
 AUTH. NOTIFY LOCAL HEALTH & POLLUTION CTL AGENCIES. (ING 5)
 Ingredient Sequence Number: 04
 Percent: N/K
 Ingredient Action Code: A
 Ingredient Focal Point: N
 NIOSH (RTECS) Number: 9999999ZZ
 CAS Number:

Report for NIIN: 00N084071

OSHA PEL: NOT APPLICABLE
 ACGIH TLV: NOT APPLICABLE
 Other Recommended Limit: N/K

 Proprietary: NO
 Ingredient: ING 4: CALL SPILL RESPONSE TEAMS IF LARGE SPILL.
 Ingredient Sequence Number: 05
 Percent: N/K
 Ingredient Action Code: A
 Ingredient Focal Point: N
 NIOSH (RTECS) Number: 9999999ZZ

CAS Number:
 OSHA PEL: NOT APPLICABLE
 ACGIH TLV: NOT APPLICABLE
 Other Recommended Limit: N/K

 Proprietary: NO
 Ingredient: RESP PROT: PARTICULATE & GAS & VAP. IN CONFINED AREAS USE
 NIOSH APPRVD AIR LINE TYPE RESPS/HOODS. RESP PROT MAY (ING 7)
 Ingredient Sequence Number: 06
 Percent: N/K
 Ingredient Action Code: A
 Ingredient Focal Point: N
 NIOSH (RTECS) Number: 999999ZZ
 CAS Number:
 OSHA PEL: NOT APPLICABLE
 ACGIH TLV: NOT APPLICABLE
 Other Recommended Limit: N/K

 Proprietary: NO
 Ingredient: ING 6: ALSO BE NECESSARY IN ANY LATER MANUFACTURING OPERATIONS
 IN WHICH PROD MAY BECOME AIRBORNE IN FORM OF VAP/DUST.
 Ingredient Sequence Number: 07
 Percent: N/K
 Ingredient Action Code: A
 Ingredient Focal Point: N
 NIOSH (RTECS) Number: 999999ZZ
 CAS Number:
 OSHA PEL: NOT APPLICABLE
 ACGIH TLV: NOT APPLICABLE
 Other Recommended Limit: N/K

=====

Physical/Chemical Characteristics

=====

Appearance And Odor: NONE SPECIFIED BY MANUFACTURER
 Boiling Point: >379F,>193C
 Melting Point: N/K
 Vapor Pressure (MM Hg/70 F): 0.10
 Vapor Density (Air=1): HVR/AIR
 Specific Gravity: N/K
 Decomposition Temperature: N/K
 Evaporation Rate And Ref: SLOWER THAN BUTYL ACETATE
 Solubility In Water: N/K

Report for NIIN: 00N084071

Percent Volatiles By Volume: 66.33
 Viscosity:
 pH: N/A
 Radioactivity:
 Form (Radioactive Matl):
 Magnetism (Milligauss):
 Corrosion Rate (IPY): N/K
 Autoignition Temperature:

=====

Fire and Explosion Hazard Data

=====

Flash Point: 241F,116C
 Flash Point Method: TCC
 Lower Explosive Limit: 3.2%
 Upper Explosive Limit: 15.3%
 Extinguishing Media: USE CARBON DIOXIDE, DRY CHEM/FOAM EXTING. NFPA CLASS

B EXTING IS DESIGNED TO EXTING NFPA CLASS 1B FLAM LIQ FIRES.
 Special Fire Fighting Proc: WEAR NIOSH APPRVD SCBA & FULL PROT EQUIP (FP
 N). WATER SPRAY MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL CLSD CONTRS TO
 PVNT PRESS BUILD-UP, POSS (SUP DAT)
 Unusual Fire And Expl Hazrds: KEEP CONTRS TIGHTLY CLSD. ISOLATE FROM HEAT,
 ELEC EQUIP, SPKS & OPEN FLAME. CLSD CONTR MAY EXPLODE WHEN EXPOSED TO
 EXTREME HEAT. DO NOT APPLY TO HOT (SUP DAT)

=====
 Reactivity Data
 =====

Stability: YES
 Cond To Avoid (Stability): AVOID EXPOSURE TO SPARKS, OPEN FLAME, HOT
 SURFACES, AND ALL SOURCES OF HEAT AND IGNITION.
 Materials To Avoid: STRONG ACIDS.
 Hazardous Decomp Products: MAY PRDCE HAZ FUMES WHEN HEATED TO DECOMP AS IN
 WELDING. FUMES MAY CONTAIN CARBON MONOXIDE & DIOXIDE & NITROGEN OXIDES.
 Hazardous Poly Occur: NO
 Conditions To Avoid (Poly): NOT RELEVANT.

=====
 Health Hazard Data
 =====

LD50-LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
 Route Of Entry - Inhalation: YES
 Route Of Entry - Skin: YES
 Route Of Entry - Ingestion: YES
 Health Haz Acute And Chronic: ACUTE/CHRONIC: RPTS HAVE ASSOC RPTD & PRLNG
 OCCUP OVEREXP TO SOLVS W/PERM BRAIN & NERV SYS DMG. INTENTIONAL MISUSE BY
 DELIB CONCENTRATING & INHALING CONTENTS MAY BE HARMFUL/FATAL. INGEST &
 EXCESS INHAL CAN BE FATAL, MAY CAUSE POSS LIVER & KIDNEY DMG. PULM EDEMA
 MAY DEVELOP W/INHAL OF HIGH CONCS. (EFTS OF OVEREXP)
 Carcinogenicity - NTP: NO
 Carcinogenicity - IARC: NO
 Carcinogenicity - OSHA: NO
 Explanation Carcinogenicity: NOT RELEVANT.
 Signs/Symptoms Of Overexp: HLTH HAZ: CAN BE IRRITATING TO EYES. MAY CAUSE
 SKIN IRRIT.
 Med Cond Aggravated By Exp: NONE SPECIFIED BY MANUFACTURER.

Report for NIIN: 00N084071

Emergency/First Aid Proc: EYES: FLUSH W/LUKE WARM WATER FOR AT LEAST 15
 MIN. SEEK MD IMMED. SKIN: FLUSH WASH W/COPIOUS AMTS OF LUKE WARM WATER.
 REMOVE CONTAM CLTHG PROMPTLY. CONT MD IMMED. INHAL: REMOVE TO FRESH AIR.
 RESTORE BRTHG IF REQUIRED. CONT MD IMMED. INGEST: RINSE MOUTH IMMED. GIVE
 6-8 OZ OF LIQ. (NEVER GIVE ANYTHING BY MOUTH TO AN UNCON PERS.) DO NOT
 INDUCE VOMIT UNLESS ADVISED BY MD. CONT MD IMMED.

=====
 Precautions for Safe Handling and Use
 =====

Steps If Matl Released/Spill: STAY UPWIND & AWAY FROM SPILL UNLESS WEARING
 APPROP PROT EQUIP. STOP &/OR CONTAIN DISCHARGE IF IT MAY BE DONE SAFELY.
 KEEP ALL SOURCES OF IGNIT AWAY. VENT AREA OF SPILL. USE NON-SPKG TOOLS FOR
 CLEANUP. COVER W/INERT MATL TO REDUCE FUMES. (ING 4)
 Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.
 Waste Disposal Method: DO NOT FLUSH TO SEWER, WATERSHED, OR WATERWAY.
 DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT
 INCINERATE CLOSED CONTAINERS.
 Precautions-Handling/Storing: KEEP CONTRS COOL, DRY & AWAY FROM SOURCES OF
 IGNIT. USE & STORE W/ADEQ VENT. DO NOT SMOKE IN STOR AREAS. AVOID INHAL OF
 VAPORS & EYE CONT.
 Other Precautions: AVOID PERSONAL CONTACT. CONTRS MAY BE HAZARDOUS WHEN

EMPTIED. SINCE EMPTIED CONTRS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN MSDS MUST BE OBSERVED. AVOID PROLONGED/REPEATED BREATHING OF VAPORS.

=====
 Control Measures
 =====

Respiratory Protection: IN OUTDOOR/OPEN AREAS USE NIOSH APPROVED MECH FILTER RESP TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATION. IN RESTRICTED VENT AREAS USE NIOSH APPROVED CHEM/MECH FILTERS DESIGNED TO REMOVE COMBINATION OF (ING 6)
 Ventilation: PROVIDE GEN DILUTION/LOC EXHST VENT IN VOL & PATTERN TO KEEP TLV BELOW ACCEPTABLE LIM, LEL BELOW STATED LIM, (SUP DAT)
 Protective Gloves: IMPERVIOUS GLOVES (FP N).
 Eye Protection: ANSI APPROVED CHEM WORKERS GOGGLES (FP N).
 Other Protective Equipment: EMERGENCY EYEWASH AND DELUGE SHOWER MEETING ANSI DESIGN CRITERIA (FP N).
 Work Hygienic Practices: REMOVE CONTAMINATED CLOTHING IMMEDIATELY AND DO NOT REUSE IT UNTIL IT HAS BEEN PROPERLY LAUNDERED.
 Suppl. Safety & Health Data: FIRE FIGHT PROC: AUTOIGNIT, EXPLO/RUPTURE WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZ ARE PREF. EXPLO HAZ: SURFS. NEVER USE WELDING/CUTTING TORCH ON/NEAR CONTR (EVEN EMPTY) BECAUSE PROD (EVEN RESIDUE) MAY IGNITE EXPLO. VENT: & TO REMOVE DECOMP PRODS DURING WELDING/FLAME CUTTING ON SURFS COATED W/THIS PROD.

=====
 Transportation Data
 =====

Transportation Action Code:
 Transportation Focal Point:
 Trans Data Review Date:
 DOT PSN Code:
 DOT Symbol:
 DOT Proper Shipping Name:

Report for NIIN: 00N084071

DOT Class:
 DOT ID Number:
 DOT Pack Group:
 DOT Label:
 DOT/DoD Exemption Number:
 IMO PSN Code:
 IMO Proper Shipping Name:
 IMO Regulations Page Number:
 IMO UN Number:
 IMO UN Class:
 IMO Subsidiary Risk Label:
 IATA PSN Code:
 IATA UN ID Number:
 IATA Proper Shipping Name:
 IATA UN Class:
 IATA Subsidiary Risk Class:
 IATA Label:
 AFI PSN Code:
 AFI Symbols:
 AFI Prop. Shipping Name:
 AFI Class:
 AFI ID Number:
 AFI Pack Group:
 AFI Label:
 AFI Special Prov:
 AFI Basic Pac Ref:

MMAC Code:
N.O.S. Shipping Name:
Additional Trans Data:

=====

Disposal Data

=====

Disposal Data Action Code:
Disposal Data Focal Point:
Disposal Data Review Date:
Rec # For This Disp Entry:
Tot Disp Entries Per NSN:
Landfill Ban Item:
Disposal Supplemental Data:
1st EPA Haz Wst Code New:
1st EPA Haz Wst Name New:
1st EPA Haz Wst Char New:
1st EPA Acute Hazard New:
2nd EPA Haz Wst Code New:
2nd EPA Haz Wst Name New:
2nd EPA Haz Wst Char New:
2nd EPA Acute Hazard New:
3rd EPA Haz Wst Code New:
3rd EPA Haz Wst Name New:
3rd EPA Haz Wst Char New:
3rd EPA Acute Hazard New:

Report for NIIN: 00N084071

=====

Label Data

=====

Label Required: YES
Technical Review Date: 23MAR98
Label Date: 23MAR98
MFR Label Number:
Label Status: M
Common Name: WEATHER BOND EXTERIOR LATEX HOUSE PAINT, G2600-30279
Chronic Hazard: YES
Signal Word: CAUTION!
Acute Health Hazard-None:
Acute Health Hazard-Slight: X
Acute Health Hazard-Moderate:
Acute Health Hazard-Severe:
Contact Hazard-None:
Contact Hazard-Slight: X
Contact Hazard-Moderate:
Contact Hazard-Severe:
Fire Hazard-None:
Fire Hazard-Slight: X
Fire Hazard-Moderate:
Fire Hazard-Severe:
Reactivity Hazard-None: X
Reactivity Hazard-Slight:
Reactivity Hazard-Moderate:
Reactivity Hazard-Severe:
Special Hazard Precautions: COMBUSTIBLE. ACUTE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENTS MAY BE HARMFUL OR FATAL. PULMONARY EDEMA MAY DEVELOP WITH INHALATION OF HIGH CONCENTRATIONS. MAY IRRITATE EYES OR SKIN. CHRONIC: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND

NERVOUS SYSTEM DAMAGE. INGESTION AND EXCESSIVE INHALATION CAN BE FATAL, MAY CAUSE POSSIBLE LIVER AND KIDNEY DAMAGE.

Protect Eye: Y

Protect Skin: Y

Protect Respiratory: Y

Label Name: ROSE TALBERT PAINT CO

Label Street: 901 FRINK ST

Label P.O. Box:

Label City: CAYCE

Label State: SC

Label Zip Code: 29033

Label Country: US

Label Emergency Number: 800-255-3924

Year Procured: