

GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067

Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **SILICLAD® GLIDE 10 - PP1-SG10**

CHEMICAL NAME: Polydimethylsilazane-Polydimethylsiloxanes and silicones mixture in isoamyl acetate

SYNONYMS: AMINE CURE SILICONE RTV

CHEMICAL FAMILY: ORGANOSILOXANE

HMIS CODES HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 1

INGREDIENTS

| IDENTITY | CAS NO. | % | ACGIH TLV | OSHA PEL |
|--|------------|-----|-----------|-----------------|
| POLY(1,1-DIMETHYLSILAZANE), telomer | 89535-60-4 | >10 | | not established |
| POLY(DIMETHYLSILOXANE), SILANOL TERMINATED | 70131-67-8 | 5 | | not established |
| ISOAMYL ACETATE | 123-92-2 | >85 | 100ppm | 100ppm |

PHYSICAL DATA

Boiling Point: 142°C- initial
Specific Gravity: 0.88
Vapor Density (air=1): 4.49 (solvent)
% volatiles: >85%
Molecular Weight: NA
Appearance & Color: Viscous liquid with amine odor

Freezing Point: <-20°C
Vapor Pressure, 20°C: not determined
Solubility in water: insoluble, reacts
Evaporation rate: NA
Other: NA

FIRE & EXPLOSION DATA

Flash Point, COC: 25°C (77°F) Autoignition Temp.: 360°C (isoamyl acetate)
Flammability Limits- (isoamyl acetate) LEL: 1% UEL: 7.5%

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.

Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes of hydrochloric acid and organic acid vapors may develop when material is exposed to water or open flame.

-1-(PP1-SG10)

ENVIRONMENTAL INFORMATION

Spill response: May be hazardous to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal.

Recommended Disposal: May be incinerated. Alternately, absorb onto clay or vermiculite and dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: Will cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation of vapors or particulates of may irritate the respiratory tract. Exposure to concentrations of about 1000ppm for i hour can cause headache, fatigue, ppulmonary irritation and other toxic effects.

Oral Toxicity (isoamyl acetate) oral-rat, LD50: 16,600mg/kg

Chronic Toxicity: No chronic organic toxicity has been observed for heptane. The volatile byproduct of cure is cyclohexylamine for which human mutagenic data have been reported.

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

REACTIVITY DATA

Stability: Stable in sealed containers stored under a dry inert atmosphere.

Conditions to avoid: Flammable; avoid contact with heat, sparks or open flame.

Incompatibility (materials to avoid): Avoid contact with oxidizers, water, alcohol.

Hazardous decomposition products: Organic acid vapors, ammonia.

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or combination organic vapor acid gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research use only.

Storage and Handling: Store in sealed containers.

TRANSPORTATION

DOT SHIPPING NAME: COATING SOLUTION (ISOAMYL ACETATE.

DOT HAZARD CLASS: 3

DOT LABEL: FLAMMABLE LIQUID

DOT ID No: UN 1139

PG: III

Prepared by safety and environmental affairs ISSUE DATE: PP1-SG10: 4/20/04
SUPERSEDES: none

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.